



Type	Alésage Extérieur		Largeur		Rayon rs(min) (millimètre)	Capacité de charge (N)		Vitesse maximale	
	Diamètre d (mm)	Diamètre D(mm)	B mm	B1 mm		Dynamique Crystallise	Statique Corps	Graisse	Huile
6815	75	95	10	10	0.60	12500	12900	12.50	12.90
6816	80	100	10	10	0.60	12700	13300	12.70	13.30
6814	70	90	10	10	0.60	12100	11900	6.80	8.10
6813	65	85	10	10	0.60	11900	11500	7.30	8.60
6811	55	72	9	9	0.60	8800	8100	8.70	10
6812	60	78	10	10	0.60	11500	10600	8	9.40
6810	50	65	7	7	0.60	6610	6090	9.60	11
6809	45	58	7	7	0.60	6187	5381	11	13
6807	35	47	7	7	0.50	4729	3821	13	16
6808	40	52	7	7	0.50	4923	4178	12	14
6806	30	42	7	7	0.50	4538	3402	15	18
6805	25	37	7	7	0.30	4303	2932	18	21
6803	17	26	5	5	0.30	2233	1456	26	30
6804	20	32	7	7	0.30	4015	2462	21	25
6802	15	24	5	5	0.30	2073	1253	28	33
6801	12	21	5	5	0.30	1915	1041	33	39
689	9	17	4	5	0.20	2467	1081	34	40
6800	10	19	5	5	0.30	1716	840	37	43
688	8	16	4	5	0.30	1252	592	36	43
687	7	14	3.50	5	0.15	1173	513	40	50
686	6	13	3.50	5	0.20	1082	442	40	50