



| Type | Alésage Extérieur | | Largeur | | Rayon rs(min) (millimètre) | Capacité de charge (N) | | Vitesse maximale | |
|------|--------------------|-------------------|---------|----------|----------------------------------|---------------------------|-------------------|---------------------|-------|
| | Diamètre d (mm) | Diamètre D(mm) | B mm | B1 mm | | Dynamique Crystallise | Statique Corps | Graisse | Huile |
| 6916 | 80 | 110 | 16 | 16 | 1 | 25000 | 24000 | 5.70 | 6.80 |
| 6915 | 75 | 105 | 16 | 16 | 1 | 24400 | 22600 | 6.10 | 7.20 |
| 6914 | 70 | 100 | 16 | 16 | 1 | 23700 | 21200 | 6.40 | 7.60 |
| 6912 | 60 | 85 | 13 | 13 | 1 | 20200 | 17300 | 7.50 | 8.90 |
| 6913 | 65 | 90 | 13 | 13 | 1 | 17400 | 16100 | 7.10 | 8.40 |
| 6911 | 55 | 80 | 13 | 13 | 1 | 16600 | 14100 | 8.10 | 9.60 |
| 6910 | 50 | 72 | 12 | 12 | 0.60 | 14540 | 11710 | 9 | 11 |
| 6909 | 45 | 68 | 12 | 12 | 0.60 | 14100 | 10830 | 9.70 | 11 |
| 6908 | 40 | 62 | 12 | 12 | 0.60 | 13678 | 9968 | 11 | 13 |
| 6907 | 35 | 55 | 10 | 10 | 0.60 | 10900 | 7818 | 12 | 14 |
| 6906 | 30 | 47 | 9 | 9 | 0.30 | 7242 | 5003 | 14 | 17 |
| 6905 | 25 | 42 | 9 | 9 | 0.30 | 7001 | 4540 | 16 | 19 |
| 6904 | 20 | 37 | 9 | 9 | 0.30 | 6381 | 3682 | 19 | 23 |
| 6903 | 17 | 30 | 7 | 7 | 0.30 | 4588 | 2565 | 23 | 38 |
| 6902 | 15 | 28 | 7 | 7 | 0.30 | 4321 | 2259 | 26 | 30 |
| 6901 | 12 | 24 | 6 | 6 | 0.30 | 2886 | 1466 | 31 | 36 |
| 6900 | 10 | 22 | 6 | 6 | 0.30 | 2695 | 1273 | 34 | 41 |
| 699 | 9 | 20 | 6 | 6 | 0.30 | 2467 | 1081 | 34 | 40 |
| 698 | 8 | 19 | 6 | 6 | 0.30 | 2237 | 917 | 36 | 43 |
| 697 | 7 | 17 | 5 | 5 | 0.30 | 1605 | 719 | 36 | 43 |
| 696 | 6 | 15 | 5 | 5 | 0.15 | 1340 | 523 | 40 | 45 |